



M.V. OFFSHORE WARRIOR

AHTS / FIFI 1 / 12,068 BHP / DP 2



REGISTRATION

Owner:	Raj Shipping Agencies Ltd.
Year Built:	2005
Builder:	Pan-United Marine, Singapore
Flag:	India
IMO Number:	9315109
Class:	Lloyd's Register of Shipping/ IRS
Classification:	<ul style="list-style-type: none"> LMC, Offshore Supply Ship, Fire-Fighting Ship 1 (2400 cu.m/hr) with water spray, LMC, DP(AA), Anchor Handling

MAIN CHARACTERISTICS

LOA:	70.7 m
Length BP:	63.0 m
Breadth (molded):	16.0 m
Depth (molded):	7.2 m
Draft (max):	6.2 m
Deadweight:	2,464 T
GRT:	2,569 T
NRT:	770 T

PERFORMANCE

Maximum Speed:	24.5 m ³ /day (270 gph) @ 13.5 knots
Cruising Speed:	10.5 m ³ /day (120 gph) @ 10 knots
Economical Speed:	7.6 m ³ /day (85.7 gph) @ 8 knots
Standby:	1.9 m ³ /day (21 gph) @ 0 knots
Range @ 10 Knots:	13,000 nm
Bollard Pull:	160 T (92.6 st / 84 mt)

CARGO CAPACITY

Deck Area:	500.0 m ² (5 T/m ²)
Deck Strength:	5.5 T/m ²
Deck Cargo Capacity:	800 T
Fuel Oil:	960.0 m ³
Potable Water:	660.0 m ³
Drill Water / SWB:	650.0 m ³ (include Chain Locker)
Liquid Mud / Base Oil / Brine:	510.0 m ³ (2 Tanks)
Dry Bulk:	285.0 m ³ (4 × 2,500 ft ³)
Chain Locker:	220.2 m ³
Foam / Dispersant:	11.7 m ³ / 12.2 m ³

DISCHARGE RATES

Fuel Oil:	1 × 120 m ³ /hr @ 80 m head
Potable Water:	1 × 120 m ³ /hr @ 80 m head

MACHINERY

Main Engines	2 × MAK 9M32C, 6,034 BHP each
Total BHP	12,068 BHP
Propeller:	2 × CPP, Kamewa 94 P1/P4T, 4-Blade
Retractable Azimuth Thruster	1 × Aquamaster UL901/4220, 725 KW, 15.0 T Thrust
Bow Thruster:	1 × 590 kW, 9.2 T Thrust
Stern Thruster:	1 × 590 kW, 9.2 T Thrust
Bollard Pull:	168 T @ 100% MCR

DYNAMIC POSITIONING SYSTEM

DP-2 System:	GEC , SEASTREAM DP System
---------------------	---------------------------

ELECTRIC POWER GENERATION

Main Generator:	2 × CAT 3412 rated 580kW/ 440V/ 60Hz/ 3Ph
Alternators:	2 × AEM SE 500 M4 rated 1,800kW/ 440V/ 60Hz/ 3Ph
Emergency Generator:	1 × CAT 305.6 T rated 99kW/ 440V/ 60Hz/ 3Ph

TOWING & ANCHOR HANDLING EQUIPMENT

AH Winch:	500 T Brake, 380 T Pull Brattvaag Double Drum Hydraulic Driven, Waterfall Type
Drum Capacity:	3,500 m × 76 mm (∅)
Chain Gypsy:	1 × 84 mm (∅), Non-Declutchable
Towing Winch:	500 T Brake, 380 T Pull Brattvaag Double Drum Hydraulic Driven, Waterfall Type
Drum Capacity:	3,500 m × 76 mm (∅)
Storage Reel Drum Capacity:	3,500 m × 76 mm (∅)
Secondary Drum Capacity:	3,500 m × 76 mm (∅)
Karm Fork:	2 × Karm Fork, SWL: 650 T
Tow Pin:	2 × Tow Pin, SWL: 650 T
Stern Roller:	5.0 m × 2.5 m (∅), SWL: 500 T

NAVIGATION & COMMUNICATION EQUIPMENT

GMDSS (Area A1):	1 × Furuno RC-1800T
VHF DSC:	1 × Furuno FM-8500 1 × FM-8900 S
MF/HF Radio:	1 × Furuno FS-2570
MF/HF DSC:	1 × Furuno FS-2570
EPIRB:	1 × McMurdo E5 Smartfind
SART:	2 × SevenStar Electronics S-701



Drill Water:	1 × 120 m ³ /hr @ 80 m head
Liquid Mud / Base Oil / Brine:	2 × 100 m ³ /hr @ 80 m head
Dry Bulk:	2 × 25.6 m ³ /min @ 5.6 bar

ACCOMMODATION

Berth / Cabin:	6 × 1 man
	9 × 2 man
	3 × 4 man
Total:	36 men



Navtex:	1 × Furuno NX-500
Portable GMDSS VHF:	3 × McMurdo R2
Inmarsat:	2 × Furuno Felcom 15
Radar:	Port - 1 × Furuno FR-1505/3365-0974 Stbd - 1 × Furuno RPU 013/4366-0726
Gyro Compass:	1 × Raytheon Anschutz STD 22, 1 × Tokimec TG-8000, 1xYokogawa GMZ-700
Magnetic Compass:	1 × Cassens & Plath Reflexa 1
Auto-Pilot:	1 × Raytheon Anschutz PilotStar D
DGPS:	2 × Fugro Seastar
Joystick:	GEC
Echo Sounder:	1 × Furuno FE-700
Speed Log:	1 × Furuno DS-80
Anemometer:	2 × RM Young
AIS:	1 × Jotron TR8000/02342

FIREFIGHTING & ANTI-POLLUTION EQUIPMENT

Fifi Class (1):	With Water Spray
Pumps:	1 × 3,200 m ³ /hr @ 140 m head
Monitor (water / foam):	2 × 1,200 m ³ /hr / 300 m ³ /hr @ 12 bar
Oil Dispersant System:	2 × 6 m Spray Boom

SAFETY EQUIPMENT

Life Rafts:	6 × 25 persons
Rescue Boat:	Port : 1 × 6 persons, NOREQ Stbd : 1 × 6 persons, Norsafe 655
Davit:	Port : GLOBAL DAVIT RHP 35/3.1 Stbd : NDM PRHE 35, SWL: 3.5 T

DECK EQUIPMENT

Anchor	1 × 18 T, Brattvaag
Windlass:	
Anchor	2 × 247.5 m × 46mm (∅)
Chain:	
Anchor (Bow)	3 × 2,280 kg Stockless Bower Anchors
Tugger Winch:	2 × 25 T @ 17 m/min, Brattvaag
Capstans:	2 × 10 T @ 19 m/min, Brattvaag
Deck Crane:	1 × TTS Marine, GPT 150-10-15, SWL: 10 T @ 8 m, 5 T @ 15 m

MISCELLANEOUS

Oily Water Separator:	1 × HELI-SEP, 1000-OCD, 1.0 m ³ /hr
Sewage Treatment:	1 × 40 persons, Hamworthy Super Trident ST3A



M.V. OFFSHORE WARRIOR

AHTS / FIFI 1 / 12,068 BHP / DP 2



ADDITIONAL NOTES / REMARKS

Anchor Handling Tug & Supply Vessel built for worldwide operations to service and tow drilling units, provide logistics support for oil & gas production platforms, with special equipments for fire-fighting, safety standby operations, emergency evacuations and seismic services. Bollard pull 160T with DP-2 Alstom Duplex system and FiFi Class 1 firefighting capability.

Particulars given here are believed to be correct but not guaranteed. Owners reserve the rights to amend the specifications without notification.